

90% OFF.

Eliminated the metal cut scrap sticking to wheel tread.

CUT RESISTANT RUBBER WHEEL XRZ



Compared to general rubber or urethane wheels, the amount of metal chips sticking to the wheel tread can be 90% reduced.

XRZ - Engineered rubber wheel - Features

- **Cut-resistant wheel** An engineered rubber wheel that prevents metal cut scrap from sticking to wheel tread.
- **Oil-resistant rubber** Oil-resistant rubber can be used in environments where it is exposed to cutting oil.*
- **Comfortable travelling** The moderate rubber elasticity, which is not found in hard wheels, enables smooth running.
- **Ball bearing installed** Ball bearing is installed to wheel bore and is available in 4 sizes: 100 mm, 125 mm, 150 mm, and 200 mm.

* Long-term use may not be possible depending on the type of oil.

Engineered rubber wheel XRZ



Cut-resistant rubber wheel
Pressed steel hub
Ball bearing

Wheel code		Size D mm	Tread width W mm	Hub width H mm	Bore d mm
Wheel No.	Wheel type				
435 S	- XRZ	100	32	45	10.0
	- XRZ	125	38	55	12.0
	- XRZ	150	40	55	12.0
	- XRZ	200	46	63	12.0

● Purple color is also available for extra non-marking property.



* Direct sunlight or ultraviolet rays may cause discoloration, but this does not affect performance or quality.

■ Product instruction video is available from below QR code.



XRZ wheel can be compatible with various type of model brackets.

Plate type

RoHS

420S Series



Caster type	Product code		Size (mm)	Load Capacity 1pc(daN)	Overall height H mm	Fitting plate A × B mm	Fitting pitch X × Y mm (X' × Y') mm	Fastening hole dia. P mm
	Model No.	Wheel						
Swivel	420 S	- XRZ	100	120	132	90 × 90	68 × 68 (71 × 71)	11
	413 S	- XRZ	125	150	168	102 × 102	75 × 75 (80 × 80)	11
Swivel with stopper	420 SR	- XRZ	100	120	132	110 × 78	80 × 45 (90 × 50)	11
	420 SRP	- XRZ	125	150	168	140 × 94	100 × 56 (112 × 53)	11
Fixed	420 SRP	- XRZ	100	120	132	90 × 90	68 × 68 (71 × 71)	11
	420 SRP	- XRZ	125	150	168	106 × 111	75 × 75 (80 × 80)	11
Fixed	420 SRP	- XRZ	150	160	190	106 × 111	75 × 75 (80 × 80)	11

400S Series



Caster type	Product code		Size (mm)	Load Capacity 1pc(daN)	Overall height H mm	Fitting plate A × B mm	Fitting pitch X × Y mm (X' × Y') mm	Fastening hole dia. P mm
	Model No.	Wheel						
Swivel	400 S	- XRZ	200	220	240	140 × 140	100 × 100 (112 × 112)	13
	419 S	- XRZ	200	220	240	150 × 105	112 × 63 (119 × 56)	13
Fixed	400 SRP	- XRZ	200	220	240	140 × 144	100 × 100 (112 × 112)	13

Threaded stem type

RoHS

420SA Series



Caster type	Product code		Size (mm)	Load Capacity 1pc(daN)	Overall height mm	Thread head mm	Stem length mm
	Model No.	Wheel					
Swivel	420 SA	- XRZ	100	120	138	M20 × 2.5	40
	413 SA	- XRZ	125	150	173	M20 × 2.5	40
	413 SA	- XRZ	150	160	196	M20 × 2.5	40

Please consult our sale offices below for more details.



● Manufacturing Factory

Headquarters factory
4-7-35, Nishi-Iwata, Higashi-Osaka, Osaka 578-0947 Japan
Hirakata factory
3-2-1, Shodaidajika, Hirakata, Osaka 573-1132 Japan

HAMMER CASTER SALES

● Hammer Caster Sales Co., Ltd. (as Sales company)

Tokyo Branch
6-5-4, Shimbashi, Minato-ku, Tokyo 105-0004 Japan
Osaka Branch
10-35, Shinjo-Nishi, Higashi-Osaka, Osaka 578-0964 Japan

■ Please feel free to ask for any caster consultancy.

E-mail : info@hammer-caster.co.jp
Web : www.hammer-caster.com

■ Click and follow our official SNS accounts.



www.facebook.com/hammercasterofficial/



www.instagram.com/hammer_caster_official/