Re-designed cushion caster in pursuit of efficiency and optimization. Your mobile carts are now for an upgrade.

Elastomer wheel is gentle to floor surfaces and does not leave scratches or stains. The synergistic effect of the built-in spring reduces harmful vibrations transmitted from the floor, gently protecting valuable cargo.





Elastomer PP hub







Shock absorbing mechanism: Built-in spring (Kick spring)



- You can choose from three types of built-in springs (set load) corresponding to the load you are using.
- The set load indicates the load that provides the best cushioning effect against vibration.
- Ball bearings are installed to swivel part on 940BBL/BLA for quieter and smoother turning performance.

Spring code	Set load (1pc)
	daN
1	8
2	14
3	20





940L series can be manufactured in a variety of mounting types and used in a wider range of fields.



HAMMER CASTER SALES

Hammer Caster Sales Co., Ltd. (as Sales company)

<mark>6-5-4, Shimbashi, Minato-ku, Tokyo 105-0004 Japan</mark>

1-2-6, Aramoto, Higashi-Osaka, Osaka 577-0023 Japan

■ Please consult our sale offices below for more details



Manufacturing Factory
 Headquarters factory
 4-7-35, Nishi-Iwata, Higashi-Osaka, Osaka, 578-0947 Japan

4-7-35, Nishi-Iwata, Higashi-Osaka, Osaka 578-0947 Japan Hirakata factory

3-2-1, Shodaidajika, Hirakata, Osaka 573-1132 Japan

Please feel free to ask for any caster consultancy. E-mail: info@hammer-caster.co.jp

Web: www.hammer-caster.com

Click and follow our official SNS accounts.

Tokyo Branch

Osaka Branch





Mini Cushion Caster

Keep calm from rattling and noise.





UPDATED;

Available in 3" wheel

its potential with 3" wheel range.

Stopper type and Fixed type are now added to enhance the lineup.



Stopper type



Built-in Kick-spring


Mini-cushion caster is added to

Achived a low-cost innovation
cushion caster lineup, expanding

with simple buffering mechanism.


Elastomer tread

New standard Elastomer wheel keeps your floor clean without any scratch or marking.













Viewab**l**e JP / EN /CN

		Product code		Set load	Overall height	Thread head	Stem length	Offset	Swivel radius
Caster type	Model No.	' y wneel	Size (mm)	1pc(daN)	H1~H2 mm	T mm	L mm	E1~E2 mm	mm
Swivel	940 LA	L	75	8~20	111~105	M12×P1.75	20	29.0~30.3	70
Swivel with stopper	935 LA	- L	75	8~20	111~105	M12×P1.75	20	29.0~30.3	70

Product feature

Cushion spring list

Cushion spring list						
Carina cada Na	Set load per pc					
Spring code No.	daN					
1	8					
2	14					
3	20					

Please specify the spring code at order.

940 L


Recommended wheel



*LZ wheel [429E-LZ75] is also available.

- Please select the built-in spring (set load) corresponding to the load at the use. ■ The set load indicates the load that provides the best cushioning effect against vibration.
- Please observe the set load.

Sectional image of the swivel part on 940L/LA series



Double thrust bearing structure is installed at the swivel section

[Quiet] Cushion Caster 940BBL

Swivel



Swivel 935BBL

940LR → Fixed

PLATE

CUSHION


QUIET

RoHS

940BBL







Caster type		Product code	2		Set load	Overall height	Fitting plate	Fitting pitch	Hole diameter	Offset	Swivel radius
custer type	Model No.	Spring code No.	Wheel	Size (mm)	1pc(daN)	H1~H2 mm	A×Bmm	X×Ymm	Pmm	€1~E2 mm	mm
Swivel	940 BBL	-	LZ	75	8~20	108~102	70×42	56×28	6.5	29.0~30.3	70
Swivel with stopper	935 BBL	-	LZ	75	8~20	108~102	70×42	56×28	6.5	29.0~30.3	70
←→ Fixed	940 LR	-	LZ	75	8~20	108~102	70×42	56×28	6.5	43.0~44.3	_


[Quiet] Cushion Caster 940BLA

CUSHION

THREAD

RoHS

940BLA (Swivel









Viewab**l**e JP / EN /CN

		Product code	e		Set load	Overall height	Thread head	Stem length	Offset	Swivel radius
Caster type	Model No.	Spring code No.	Wheel	Size (mm)	1pc(daN)	H1~H2 mm	T mm	L mm	€/ E1~E2 mm	mm
Swivel	940 BLA -		LZ	75	8~20	111~105	M12×P1.75	20	29.0~30.3	70
Swivel with stopper	935 BLA -		LZ	75	8~20	111~105	M12×P1.75	20	29.0~30.3	70

Product Specification

Cuchion enring list

Custilon spring list						
Consider and a Nice	Set load per pc					
Spring code No.	daN					
1	8					
2	14					
3	20					

Please specify the spring of	couc	e at order.		
Order example				
Bracket No. Series No.		Spring Code No.	Wheel type Wheel	size
QAORRI		7	177	5
34000L	_			J


LZ wheel (429E-LZ75)

PP hub

%L wheel [429E-L75] is also available.

- Please select the built-in spring (set load) corresponding to the load at the use. ■ The set load indicates the load that provides the best cushioning effect against vibration.
- Please observe the set load.

Sectional image of the swivel part on 940BBL/BLA series



Ball bearings are installed for quiet and smooth turning.